

PM43/PM43c/PM23c Mid-Range Industrial Printers

The PM43 and even more compact PM43c Mid-Range Industrial Printers deliver fast print speeds, drop-in deployment, advanced connectivity and proven reliability. Built to deliver maximum uptime, PM series printers are available with either a tamper-proof color touchscreen in 10 languages, or a universal icon interface. This enables immediate notifications through the printer interface, reducing your workforce training and device support needs.

As one of the most "connected" industrial printers on the market, the PM series feature Wi-Fi and Cisco® CCX certifications, with additional Bluetooth® connectivity. Every printer ships with Ethernet connectivity, as well as network protocol IPv6, ensuring long-term enterprise scalability.

As a third-generation industrial printer platform, rugged PM series printers incorporate features that increase uptime and reduce maintenance costs. A strong, metal construction is perfect for harsh industrial environments. And with Precision Print, even the smallest barcodes and images can be printed with pinpoint accuracy – no frequent media adjustments necessary.

Each PM43, PM43c and PM23c printer has an integrated web interface that allows for easy setup, monitoring and configuration through devices like handheld computers, tablets or smartphones. Integrated device management and diagnostic capabilities, provided through the Honeywell SmartSystems™ Foundation and Wavelink Avalanche®, reduce downtime and simplify deployment.

With very fast print speeds up to 12 ips, you'll gain a clear productivity advantage. But performance isn't about just



The PM series printers are ideal for a wide range of applications within the distribution center, warehouse, manufacturing, transportation and retail environments.

speed; it's also about working smarter. The PM series printers are intelligent, helping you to reduce labeling errors and increase process efficiencies. In-printer apps, developed with Honeywell C# for Printers, can directly control other devices such as scanners, scales, keyboards and other peripherals – without the need for an attached computer.

With their user-selectable, all-in-one programming languages, PM series printers fit into most IT infrastructures, deploying quickly into existing Honeywell or mixed printer environments.

The PM series printers are co-engineered and tested with Honeywell Media Products, ensuring optimized printhead performance when used with genuine Honeywell media.

FEATURES & BENEFITS



Large color multilingual tamper-proof touchscreen or icon user interface.



Ready for the future, with IPv6 support, plus CCX and Wi-Fi certifications.



Built-in multilingual web interface on every printer for easy device monitoring.



Fast printing speed of up to 12 inches per second.



Run sophisticated apps right in the printer with industry-leading Honeywell Smart Printing supporting C#.

PM43/PM43c/PM23c TECHNICAL SPECIFICATIONS

DESCRIPTION

Industrial mid-range, direct thermal and thermal transfer label, ticket and tag printer. Also available with RFID.

PHYSICAL CHARACTERISTICS

PM43: LxHxW: 483 x 295 x 284 mm (19.0 x 11.6 x 11.2 in); Weight: 15.82 kg (34.88 lbs)

PM43c: LxHxW: 431 x 181 x 253 mm (17.0 x 7.1 x 9.9 in); Weight: 12.5 kg (27.65 lbs)

PM43c with Dome Door:

LxHxW: 500 x 245 x 253 mm (19.6 x 9.6 x 9.9 in); Weight: 12.71 kg (28.02 lbs)

PM23c: LxHxW: 431.84 x 181 x 205.5 mm

(17 x 7.13 x 8.09 in)

PM23c with Dome Door: LxHxW: 500.22 x

244.87 x 205.5 mm (19.69 x 9.64 x 8.09 in)

PM23c with Bag Tag Door: LxHxW: 431.84 x

207 x 205.5 mm (17 x 8.15 x 8.09 in);

Weight: 9.5 kg (21 lbs)

PM43/43C PRINT SPECIFICATIONS

Max. Width at 203 dpi: 108 mm (4.25 in)

Max. Width at 300 dpi: 106 mm (4.17 in)

Max. Width at 406 dpi: 104 mm (4.09 in)

Max. Length at 203 dpi: 4.8 m (15.75 ft)

Max. Length at 406 dpi: 1.2 m (3.94 ft)

PM23C PRINT SPECIFICATIONS

Max. Width at 203 dpi: 56 mm (2.2 in)

Max. Width at 300 dpi: 106 mm (4.17 in)

Max. Width at 406 dpi: 64 mm (2.5 in)

RFID STANDARDS & FREQUENCIES

18000-6C / EPC Class 1 Generation 2

865–928 MHz radio configured to comply with local UHF RFID regulations including FCC and ETSI. Contact local representative for availability in particular regions.

PRINT SPEED

At 203/300 dpi: 100–300 mm/s (4–12 ips)

At 406 dpi: 100–250 mm/s (4–10 ips)

PRINT RESOLUTION

At 203 dpi: 8 dots/mm

At 300 dpi: 11.8 dots/mm

At 406 dpi: 16 dots/mm

MEDIA

Type: Labels and Tags, Linerless and Lined media

PM43/43c Max/Min Width:

114/19 mm (4.5/0.75 in)

Thickness: 3 to 10.4 mil

PM23c Max/Min Width: 68/19 mm (2.7/0.75 in)

Configuration: Roll-fed or fanfold

Sensing: Gap, notch, black mark, continuous

Label Roll Max. Diameter: 152 mm (6 in) for long

door models; 213 mm (8.38 in) for all other models

Label Roll Core: 38–76 mm (1.5–3 in)

Type: Ribbons

PM43 Roll Max. Diameter:

80 mm (3.15 in), approx. 450 m

PM23/43c Roll Max. Diameter:

61 mm (2.40 in), 229 m

Core ID: 25 mm (1 in)

Type: Wax, mid-range, resin

Genuine Honeywell Media:

www.honeywellaidc.com/media

INTERFACES

Standard:

- Ethernet 10/100 Mbps
- RS-232, up to 115.2 KB/s
- Supported Serial Protocols:
 - Fingerprint/Direct Protocol: XON/XOFF, ENQ/ACK, DSR/DTR, RTS/CTS
 - IPL: XON/XOFF, Honeywell Std. Protocol

- USB 2.0

- USB Host (X1 on PM23c/PM43c, X2 on PM43)

Optional:

- Parallel IEEE 1284
- Industrial Interface (8 digital in/out, 4 analog relays, 1 RS232/422/485 port)
- Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop
- Dual USB Host

Wireless:

- IEEE 802.11 b/g/n + Bluetooth
- Wi-Fi Certified, CCX (Cisco) version 4 Certified
- Static WEP (64 bit and 128 bit), Dynamic WEP (TLS, TTLS, PEAP, LEAP, EAP-FAST), WPA (TKIP/CCKM Personal and Enterprise), WPA2 (AES-CCMP/CCKM Personal and Enterprise)

- Multiple industrial antenna options for maximized coverage

Supported Protocols:

- TCP/IP suite (TCP, UDP, ICMP, IGMP), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMPv1/2c/3, SNMP-MIBII supported – over UDP/IP (private enterprise MIB included), SMTP
- Supports IPv4 and IPv6

SOFTWARE

Printer Command Languages:

- IPL, DP, ZSim (ZPL), DSim (DPL)
- XML enabled for SAP® All and Oracle® WMS

Applications/Drivers:

- InterDriver Windows® printer driver
- Honeywell Certified Device Types for SAP
- Honeywell label design and print package
- Smart Printing Languages:
 - Honeywell C# for Printers
 - Smart Printing Developer Resource Kit
 - Write apps with .NET-compatible development environments

- Honeywell Fingerprint

– Use Honeywell Fingerprint ApplicationBuilder

Configuration & Device Management Support:

- PrintSet for printer configuration

- SmartSystems for remote management
- Sophisticated web interface for configuration, upgrade and 1:1 management
- Wavelink Avalanche

BAR CODE SYMBOLOGIES

All major 1D and 2D symbologies are supported.

STANDARDS SUPPORTED

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); OGMARS; POSTNET; HIBCC; ISBT 128; GM1724; UPS Shipping label; Global Transport Label

FONTS

Monotype font engine

Non-Latin fonts available through WTLÉ

GRAPHICS

Supports PCX, PNG, GIF and BMP file formats.

Other formats supported with Label Generation Tools.

MEMORY

Standard: 128 MB Flash memory, 128 MB SDRAM, Multi-GB USB memory device (FAT16/FAT32)

USER INTERFACE

Color Touch UI, Icon UI

USER INTERFACE LANGUAGES

On Color Touch LCD and Web Interface: English, Russian, German, French, Portuguese, Spanish, Italian, Korean, Simplified and Traditional Chinese

POWER SUPPLY

AC Voltage: 100 to 240 VAC, 45 to 65Hz

PFC Regulation: IEC320/C14

Power Consumption: Standby 9W; Peak 300W

OPERATING ENVIRONMENT

Ambient Operating Temperature:

+5°C to +40°C (+41°F to +104°F)

Storage Temperature:

-20°C to +70°C (-4°F to +152°F)

Humidity: 20 to 80% non-condensing

REGULATORY APPROVALS

RoHS Compliant, CE (EN55022 Class A), FCC Class A, UL/cUL, D Mark and CCC

OPTIONS AND ACCESSORIES

Consult the PM Series Accessory Guide for full details: Integral self-strip unit with liner takeup, label taken sensor (LTS), media low sensor, media supply hub, parallel interface board, real-time clock, RFID UHF, additional serial interface boards¹, industrial interface boards¹, collapsible ribbon and liner core², cutter², linerless², full batch label/liner rewinder³

1 Not applicable when using IPL firmware.

2 Compatible with PM43 and PM43c only.

3 Compatible with PM43 only.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies.

Cisco is a trademark or registered trademark of Cisco Systems, Inc. in the United States and/or other countries.

Bluetooth is a trademark or registered trademark of Bluetooth SIG in the United States and/or other countries.

SmartSystems is a trademark or registered trademark of Honeywell International Inc. in the United States and/or other countries.

Wavelength Avalanche is a trademark or registered trademark of Wavelength Corporation in the United States and/or other countries.

SAP is a trademark or registered trademark of SAP SE in the United States and/or other countries.

Oracle is a trademark or registered trademark of Oracle Corporation in the United States and/or other countries.

Windows is a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries.

Honeywell Scanning & Mobility

9680 Old Bailes Road

Fort Mill, SC 29707

800-582-4263

www.honeywell.com

PM43-DS Rev F 06/15

© 2015 Honeywell International Inc.