



Zebra® Advanced Desktop Printers



SEE MORE. DO MORE.

- GK420t™ (direct thermal/thermal transfer)
- GK420d™ (direct thermal)
- GT800™ (direct thermal/thermal transfer)



Advanced, Affordable and Flexible

Zebra's advanced line of desktop printers features professional-quality, reliable printing at a competitive price. Dependable performance and advanced features—along with fast print speeds, network manageability and easy-load designs—enable users to improve operational efficiencies, boost profitability and reduce downtime.

The advanced line is flexible, making it a top choice for a variety of mid-volume and distributed-printing applications. Reliably producing quality text, barcodes or graphics, the advanced line offers three connectivity interfaces and easy upgrades with ZPL® and EPL™ programming languages.

The GK420t and GT800 offer direct thermal and thermal transfer

printing power in sleek and compact designs. The GT800 features a 300-meter ribbon for fewer ribbon changes along with a standard moveable sensor. Additional GT800 options include 300 dpi and a full-width cutter or peel dispenser. The GK420d offers only direct thermal printing.

For healthcare-specific environments, Zebra offers the GK420 Healthcare printer—available in both thermal transfer and direct thermal models. These printers feature disinfectant-ready plastics to protect patient safety along with a medical-grade power supply that meets IEC 60601-1 standards to reduce the risk of electrical shock.

A small footprint and affordable quality make these advanced printers an excellent choice for companies worldwide.

Ideal for These Applications

Healthcare: patient identification, pharmacy and product labeling

Retail: price marking, coupon and receipt printing, inventory and product labeling

Transportation & Logistics: shipping labels

Hospitality & Leisure: boarding passes, bag tags

Security: visitor ID, evidence tracking, parking passes

SPECIFICATIONS AT A GLANCE*

Printer Name

GK420t
GK420d
GT800 (not available in North America)

Standard Features

- Print methods: Thermal transfer or direct thermal
- Programming language: EPL™ and ZPL® are standard construction: Dual-wall frame
- Tool-less printhead and platen replacement
- OpenACCESS™ for easy media loading
- Quick and easy ribbon loading
- Auto-calibration of media
- Triple connectivity: USB, Parallel, Serial
- 300 meter ribbon capacity (GT800 Model only)
- 32 bit RISC processor (GT800 Model only)
- Certified Microsoft® Windows® drivers
- ENERGY STAR® qualified

Printer Specifications

Resolution

- 203 dpi/8 dots per mm
- Optional 300 dpi/12 dots per mm (GT800 Model only)

Memory

- GT800 Model: 8MB Flash, 8MB SDRAM
- G-Series GK Models: 4MB Flash, 8MB SDRAM (standard)

Print Width

4.09"/104 mm

Maximum Print Length

39"/991 mm

Maximum Print Speed

- 5"/127 mm per second (203 dpi)
- 4"/102 mm per second (300dpi, GT800 Model only)

Media Sensors

- GT800 Model: Multi-position transmissive and full-width reflective sensor
- G-Series GK Models: Fixed reflective and transmissive sensors

Media Characteristics

- Maximum Media Roll Size: 5"/127 mm O.D. on a 1"/25.4 mm, 1.5"/38 mm I.D. core
- Media Thickness: 0.003"/0.08 mm ~ 0.007"/0.18 mm

GT800 Model

- Media Width: 0.75"/19 mm to 4.49"/114 mm
- Media Length: 0.25"/6.5 mm to 39"/991 mm
- Media Types: Roll-fed or fan-fed, die cut or continuous direct thermal labels with or without black line, tag stock, continuous receipt paper, wristbands, and liner-free direct thermal media

G-Series GK Models

- Maximum Label and Liner Length: Maximum non-continuous: 39"/991 mm
- Maximum non-continuous: 39"/991 mm
- Maximum Label and Liner Width: 0.75"/19 mm to 4.25"/108 mm
- Media Types: Roll-fed or fan-fed, die-cut or continuous direct thermal labels with or without black line, tag stock, continuous receipt paper, wristbands

Ribbon Characteristics

GT800 Model

- Outside Diameter: 2.6"/66 mm (300 m); 1.34"/34 mm (74 m)
- Standard Length: 984' (300 m); 244' (74 m)
- Ratio:
 - 1:4 media to roll to ribbon (300 m)
 - 1:1 media to roll to ribbon (74 m)
- Width: 1.33"/33.8 mm ~ 4.3"/110 mm
- Core I.D.:
 - 300 m ribbon 1"/25.4 mm
 - 74 m ribbon 0.5"/12.7 mm

G-Series GK Models

- Outside diameter: 1.36"/35 mm
- Standard length: 244'/74 m
- Ratio: 1:1 media to roll to ribbon
- Width: 1.33"/33.8 mm to 4.3"/109.2 mm
- Core inner diameter: 0.5"/12.7 mm

Operating Characteristics

Environmental

- Operating Temperature: 40° F/4.4° C to 105° F/41° C
- Storage Temperature: -40° F/-40° C to 140° F/60° C
- Operating Humidity: 10% to 90% non-condensing
- Storage Humidity: 5% to 95% non-condensing

Electrical

- Auto-detectable (PFC Compliant) 100-240VAV, 50-60Hz
- ENERGY STAR qualified printers

Agency Approvals

GT800 Model

TUV-R NRTL, TUV-R CB, NOM, KCC, CE, FCC Class-B

G-Series GK Models

- Emissions: FCC Part 15, Subpart B (Class B), ICES 003, VCCI, C-Tick, CQC, EAC, KCC, BSMI, ICES-003
- Emissions and Susceptibility: EN55022 (Class B), EN55024, EN61000-3-2, EN61000-3-3
- Safety: CB Scheme IEC 60950-1, TUV NRTL, C-Tick, CCC, NOM, EAC, KCC, BSMI, BIS

Physical Characteristics

GT800 Model

- Width: 7.75"/197 mm
- Height: 7.25"/184 mm
- Depth: 10.75"/273 mm
- Weight: 5.8 lbs/2.63 kg

G-Series GK Models

- | | Direct Thermal | Thermal Transfer |
|-----------|----------------|------------------|
| • Width: | 6.75"/171 mm | 7.6"/193 mm |
| • Height: | 6.0"/152 mm | 7.5"/191 mm |
| • Depth: | 8.25"/210 mm | 10.0"/254 mm |
| • Weight: | 3 lbs/1.4 kg | 4.6 lbs/2.1 kg |

Fonts/Graphics/Symbologies

Fonts and Character Sets

- 16 resident expandable ZPL fonts
- One resident scalable ZPL font
- 5 resident expandable EPL2 fonts
- Supports user-defined fonts and graphics — including custom logos (GT800 Model)
- Native open type font support (G-Series GK Models)
- Unicode™ compliant for multi-language, on-demand thermal printing (G-Series GK Models)

Options and Accessories

- Dispenser: Label peel and present with label present sensor
- Full-width cutter (GT800 Model)
- ZebraNet 10/100 Print Server: Internal Ethernet for network communication and printing
- ZKDU™ and KDU Plus™ keyboard display units for stand-alone printing solutions
- Font Packs—Asian and other international font kits (G-Series GK Models)
- 300 dpi/12 dots per mm (GT800 Model)

Barcode Symbologies

- Bar Code Ratios: 2:1 (non-rotated) and 3:1
- Linear Bar Codes: Codabar, Code 11 (ZPL), Code 128, Code 39, Code 93, Code 93, EAN-13, EAN-8, EAN-14 (ZPL), German Post Code (EPL), Industrial 2-of-5 (ZPL), Interleaved 2-of-5, Japanese Postnet (EPL), ISBT-128 (ZPL), Logmars (ZPL), MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5 (ZPL), UCC/EAN-128 (EPL), UPC and EAN 2 or 5 digit extensions (ZPL), UPC-A, UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E, and GS1 Databar (formerly RSS)
- 2-Dimensional: Codablock (ZPL), Code 49 (ZPL), Data Matrix, MaxiCode, QR Code, PDF417, MicroPDF417, Aztec (for EPL and ZPL except where noted)

Communication and Interface Capabilities

- Centronics® Parallel (36 pin) connector ports
- RS-232 Serial interface
- USB V1.1 interface, bi-directional
- Optional Ethernet—10/100 internal (replaces Serial and Parallel ports in G-Series GK Models; replaces Parallel port in GT800 Model)

Zebralink™ Solutions

Software

- ZebraDesigner™ Pro
- ZebraDesigner
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v7.0
- ZBI-Developer™

GT800 Model

- Zebra Setup Utilities

G-Series GK Models

- ZebraDesigner Windows Driver
- POS Driver

Networking Options

Ethernet - 10/100 internal (optional)

Firmware

- ZPL II®
- EPL2™
- Web View
- Alert

GT800 Model

- ZBI 2.0™ (optional)

G-Series GK Models

- EPL Line Mode (direct thermal only)
- ZBI™



Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
apacchannelmarketing@zebra.com

EMEA Headquarters
+44 (0)1628 556000
mseurope@zebra.com

Latin America Headquarters
+1 847 955 2283
inquiry4@zebra.com

Other Locations / USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom **Asia Pacific:** Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, Philippines, Singapore, South Korea, Taiwan, Thailand, Vietnam **Latin America:** Argentina, Brazil, Colombia, Florida (LA Headquarters in USA), Mexico **Africa/Middle East:** Dubai, South Africa

*Specifications subject to change without notice.

©2015 ZIH Corp. All rights reserved. All product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic, ZPL, ZPL II and ZebraNet are registered trademarks of ZIH Corp. All rights reserved. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Centronics is a registered trademark of Centronics Data Computer Corporation. ENERGY STAR and the ENERGY STAR mark are registered marks owned by the U.S. government. All other trademarks are the property of their respective owners.

(1/15)