

PRODUCT SPEC SHEET

ZEBRA® VC80 VEHICLE MOUNT MOBILE COMPUTER



ZEBRA



Zebra® VC80

Vehicle Mount Mobile Computer

GET THE FULL WINDOWS SUPPORT YOU NEED TO PUT YOUR DESKTOP APPLICATIONS AT THE FINGERTIPS OF YOUR VEHICLE OPERATORS

With the VC80, you can give operators in material handling vehicles mobile access to the desktop applications they need to complete tasks faster and more accurately. You get full Windows support in a super rugged design built for your toughest indoor and outdoor environments — from warehouses and distribution centers to airports, seaports, railway yards and more — plus the fastest wireless connections available to keep workers connected to your data and productive.

And with its compact design and flexible mounting options, it's easy to install in forklifts, clamp trucks, yard mules, cranes and more. The VC80 — real desktop power to handle your mobile application needs.

PUT REAL DESKTOP POWER IN YOUR WAREHOUSE VEHICLES WITH THE VC80.

For more information, visit www.Zebra.com/VC80 or access our global contact directory at www.zebra.com/contact

The VC80 is ideal in... Industries

- Warehousing
- Distribution
- Transportation & Logistics
- Manufacturing

Environments

- Freezers
- Outdoor yards
- Airports
- Seaports
- Railway yards

Applications

- Receiving
- Picking
- Packing
- Shipping
- Replenishment
- Cross-dock
- Work in Process (WIP)

PRODUCT SPEC SHEET

ZEBRA® VC80 VEHICLE MOUNT MOBILE COMPUTER

Compact Design and Flexible Mounting Options.

Real desktop power to handle your mobile application needs.



FREEZER-READY FOR THE COLDEST SUPPLY CHAIN

You get true frost and condensation free operation with touchscreen, board and battery heaters, plus smart temperature sensors that automatically control heater and heating speed.

MAXIMUM RUGGED DESIGN

The VC80 is ready for your toughest environments, with dust-and-water tight IP66 sealing, sealed connectors, and extreme temperature, shock and vibration testing.

EASY TO SEE INDOORS AND OUTSIDE

Choose either 1,000NITS for a super bright screen that is easy to see outdoors or 400NITS for indoor operation.

PROGRAMMABLE KEYS TO SIMPLIFY THE MOST COMPLEX OPERATIONS

With six direct and six soft programmable keys, multi-step processes can be executed with one keypress, boosting throughput and productivity.

DESIGNED FOR VOICE IN YOUR LOUDEST ENVIRONMENTS

The very loud front facing speaker and instantly accessible volume control make it easy to hear scanner feedback and app notifications.

PRODUCT SPEC SHEET

ZEBRA® VC80 VEHICLE MOUNT MOBILE COMPUTER

FITS IN VIRTUALLY ANY WAREHOUSE/MATERIAL HANDLING VEHICLE

Multiple mounting options, including standard RAM mounts combine with a compact size for an easy fit and easy mounting, even in the smallest vehicles. And a 10-second quick release mount makes it easy to move the VC80 to another vehicle during vehicle maintenance or device repair.

FLEXIBLE DATA ENTRY — TOUCH OR OPTIONAL KEYBOARD

The touchscreen's soft keyboard and haptic vibration feedback make it easy to use touch input, even with the thickest gloves. Or you can choose to mount an optional keyboard on the bottom or side of the VC80.

POWER TO SUPPORT TODAY'S GRAPHICS-INTENSIVE APPLICATIONS

Get the power you need to deliver blazing speed for your applications with your choice of a dual core 1.33GHz with 2GB RAM or a quad core 1.91GHz processor with 4GB RAM.

SUPERIOR FLEXIBILITY — ADD BAR CODE SCANNING, VOICE AND MORE

Different workers need different capabilities. That's why the VC80 offers all the ports you need to add bar code scanners, mobile printers, a push-to-talk microphone and more.



ROCK-SOLID FAST WI-FI CONNECTIVITY

With support for the latest Wi-Fi standards — 802.11a/b/g/n/ac — plus a choice of internal or external antennas, the VC80 can deliver desktop wired-line style performance on the most complex applications.

REPAIRABLE, RIGHT ON THE SPOT

Since the touchscreen — the most frequently damaged component — is field replaceable, trips to the service depot are eliminated, increasing device availability and your return on investment.

PAIR BLUETOOTH DEVICES IN A SPLIT SECOND

Need a separate handheld scanner? With a quick scan of the pairing bar code printed on the VC80 with Zebra's LS3478 or DS3578 handheld or RS507 ring-style cordless scanners, your workers are up and running.

COMPREHENSIVE WINDOWS OPERATING SYSTEM (OS) SUPPORT

The VC80 supports Embedded Standard 7 or Windows 7 Professional, and is Windows 10 ready, making it easy to extend virtually any PC-based app to your material handling vehicles.

PRODUCT SPEC SHEET

ZEBRA® VC80 VEHICLE MOUNT MOBILE COMPUTER

Specifications Chart*

PRODUCT NAME		PERFORMANCE CHARACTERISTICS		WIRELESS DATA COMMUNICATIONS	
VC80		CPU and RAM Intel E3825 Dual Core, 1.33 GHz with 2 GB RAM or Intel E3845 Quad Core, 1.91 GHz with 4 GB RAM		WLAN IEEE 802.11a/b/g/n/ac 2x2 MIMO	
PHYSICAL CHARACTERISTICS		Operating System <ul style="list-style-type: none"> Windows Embedded Standard 7, 64 bit Windows 7 Professional, 64 bit Windows 10 ready 		WLAN Antennas Internal or external	
Dimensions	10.4 (L) x 9.3 (W) x 3.5 (D)"/ 265 (L) x 235 (W) x 90 (D)mm	Mass Storage mSATA SSD: 32 or 64 GB		WPAN <ul style="list-style-type: none"> Bluetooth V2.1 + EDR (Window 7/10) Bluetooth V4.0 Smart Ready (Windows 10) 	
Weight	8.6 lbs./ 3.9kg	Internal Expansion Slots <ul style="list-style-type: none"> Two (2) PCIe mini slots (one standard, one optional) One (1) M.2 slot 		GPS Optional with DGPS support	
Keyboard Options	External QWERTY and AZERTY, optional L-mount	Additional Software <ul style="list-style-type: none"> My-T-Soft configurable on-screen keyboard Scanner Wedge with code manipulations Scanner Management Service (SMS) 		VOICE AND AUDIO	
Power	Internal power supply 12-48V nominal, designed for forklift power	Optional Software <ul style="list-style-type: none"> Wavelink Terminal Emulation (TE) 3270, 5250, VT100, VT220 (pre-loaded and pre-licensed on specific models) TekTerm Mobile Device Management 		Audio High volume 87 dBA speaker	
UPS and Backup Battery	Rechargeable UPS battery for operation during power loss; internal rechargeable battery for multiple months of real-time clock backup	Application Development Standard Windows plus WMI additions		Push-to-Talk External optional speaker/ microphone	
Display	<ul style="list-style-type: none"> 10.4" color XGA (1024 x 768) LCD 24-bit color depth Choice of 400 or 1,000 NITs LED backlight 	USER ENVIRONMENT		REGULATORY	
Touchscreen	Resistive touchscreen with passive stylus or finger operation Freezer version: integrated touchscreen heater evaporates external condensation when moving out of and into freezers	Operating Temperature -22~122°F/ -30~50°C		Electrical Safety <ul style="list-style-type: none"> Indoor use: UL/cUL/IEC/EN 60950-1 Outdoor use: UL/cUL/IEC/EN 60950-22 	
Keys	<ul style="list-style-type: none"> Six (6) programmable macro keys Keyboard key Volume Brightness Blue key for 2nd level functions On/off key 	Storage Temperature -22~140°F/ -30~60°C		EMI/RFI <ul style="list-style-type: none"> North America: FCC Part 15, Class B Canada: ICES 003 Class B EU: EN55022, EN 301 489-1, EN 301 489-17 	
Interface Ports	<ul style="list-style-type: none"> Standard sealed and secured connectors 2 RS-232 serial ports 1 standard USB port 1 powered USB port 13.5 mm audio jack Optional Ethernet (10/100/1000 Mbps) or isolated CAN port with SAE J1939 support 	Humidity <ul style="list-style-type: none"> Standard version: 5%~95% non-condensing Freezer version with internal heating: 5%~95% condensing 		WLAN/Bluetooth <ul style="list-style-type: none"> USA: FCC Part 15, 247, 15.407 Canada: RSS-210 EU: EN 300 328, EN 301 893 AU/NZ: AS/NZS 4268 	
Indicators	<ul style="list-style-type: none"> Power LED Warning LED Blue key status LED 	Sealing IP66		Environmental RoHS/WEEE/REACH compliant	
Scanner Support	Handheld scanners and imagers connected via USB, RS-232 or Bluetooth	Thermal Shock -22~122°F/ -30~50°C		Flammability IEC UL94-V0	
Mounting	<ul style="list-style-type: none"> Quick release mount Standard RAM mounts Adapters for legacy vehicle computer mounts 	Shock/Vibration <ul style="list-style-type: none"> IEC 60721-3-5M3 MIL-STD 810G Method 514.6 MIL-STD 810G Method 516.6 		ACCESSORIES	
		Salt Fog 48 hours of 5% solution at 35°C		<ul style="list-style-type: none"> Corded scanners Cordless scanners Antennas Push-to-talk speaker/ microphone Keyboards Keyboard mounts Adaptation kits (power cables) for drop in replacements of legacy vehicle mount computer installations Quick release mount RAM mounts Scanner holder 	
		Solar Radiation <ul style="list-style-type: none"> MIL STD 810-G Method 505.5 Procedure I 		For a complete list of accessories, visit: www.zebra.com/vc80	
		Integrated Sensors <ul style="list-style-type: none"> Motion (accelerometer) Temperature Ignition 		WARRANTY	
		ESD <ul style="list-style-type: none"> ±15kV air discharge ±8kV direct discharge 		Subject to the terms of Zebra's hardware warranty statement, the VC80 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment.	
				For complete warranty statement, please visit: http://www.zebra.com/warranty	
				RECOMMENDED SERVICES	
				Zebra OneCare Select	



Asia-Pacific Headquarters | +65 6858 0722 | contact.apac@zebra.com

*Specifications subject to change without notice. ©2015 ZIH Corp and/or its affiliates. All rights reserved. Zebra and the stylized Zebra head are trademarks of ZIH Corp registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. 12/2015 (AP)